

526133-060/W



SELF-ADHESIVE PROTECTION FILM

Product description The film 526133-060/W is recommended for the protection of sensitive surfaces against dirt and damage during processing, storage and mounting.

Application The film is used for protecting of surfaces:
- very structured surfaces

Technical data

Carrier Polyethylene
Carrier colour transparent
Total thickness [mm] 0,060
Application temperature °C 10°C to 40°C
Adhesive (inner side) Solvent acrylic
Adhesion to stainless steel 3,2 N/cm; AFERA 4001 modified
resistance to moisture High
resistance to oil Moderate
Resistance to solvents Moderate
UV resistance 150h QUV-Test*

Storage Store at temperatures between 10°C to 40°C
Storage maximum 6 months from production date.
Do not expose to direct sunlight and humidity.

Notes on application Film must be removed from the product not later than specified UV resistance.
Film should be removed at temperatures above +10 °C.

*150h is equal to 3 months exposure in Wipperfuerth/Western Europe - producer headquarters.

Surface must be free from oil, fat, dust and solvents before film/tape application. Do not use cleaners containing anti-adhesive agents. Some plastics and paints may discharge anti-adhesive agents leading to bonding failure. Rough and uneven surfaces may weaken bonding. Product should be stored in original packaging, laid flat on the slit edge of the roll. Storage in dry and clean areas, at normal temperature, protected from direct sunlight and heat sources.

Statements, technical information and recommendation contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and assumes all risk and liability whatsoever in connection therewith.