

568-080/W



SELF-ADHESIVE PROTECTION FILM

Product description S/A protection film 568-080/W is used to protect surface from dirt and damage during treatment, storage and assembly.

Application The film is used for protection of surfaces:
-lacquered, rough and structured surfaces, matt.

Technical data

Carrier Polyethylene
Carrier colour black / white
Total thickness [mm] 0,080
Adhesive (inner side) Solvent acrylic
Adhesion to stainless steel 3,9 N/cm +2/-1 N/cm; AFERA 4001 modified
resistance to moisture Good
Resistance to oil Moderate
Resistance to solvents Moderate
Resistance to UV 300h QUV-Test*
Storage Store at temp. 10 °C to 40 °C.
Storage maximum 6 month from production date.

Notes on application Do not expose to direct sun light and moisture.
Film should be removed at temperatures above +10 °C.

*300hrs QUV-test conform to 6 month outside exposure at Wipperfürth / Western Europe climate.

Surface must be free from oil, fat, dust and solvents before film/tape application. Do not use cleaners containing anti-adhesive agents. Some plastics and paints may discharge anti-adhesive agents leading to bonding failure. Rough and uneven surfaces may weaken bonding. Product should be stored in original packaging, laid flat on the slit edge of the roll. Storage in dry and clean areas, at normal temperature, protected from direct sunlight and heat sources.

Statements, technical information and recommendation contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and assumes all risk and liability whatsoever in connection therewith.